

ATEMPERADORES

TEMPERATURE CONTROL UNITS

TEMPERIERGERÄTE

MODELOS BOMBAS / PUMP MODELS / PUMP MODELLES

	MICROHEAT	SMART	SMART 2 W	SMART 2 A	SMART 2 WDC	SMART 2 WIC	SMART 4 W	SMART 4 A	SMART 4 WDC	SMART 4 WIC	SMART 6 W	SMART 6 A	SMART 6 A 300	SMART 6 WIC
C221C - Temp. 140°C Max. Flow 110 lit/min Max. pressure 1,8 bar	●	-	-	-	-	-	-	-	-	-	-	-	-	-
NM1 - Temp. 90°C Max. Flow 70 lit/min Max. pressure 2,2 bar	-	-	-	-	●	-	-	-	-	-	-	-	-	-
NM2512 - Temp. 90°C Max. Flow 200 lit/min Max. pressure 2,5 bar	-	-	-	-	-	-	-	-	●	-	-	-	-	-
NM25160 - Temp. 90°C Max. Flow 200 lit/min Max. pressure 3,7 bar	-	-	-	-	-	-	-	-	0	-	-	-	-	-
VA 5 1-100 - Temp. 90°C Max. Flow 60 lit/min Max. pressure 3,5 bar	-	●	-	-	-	-	-	-	-	-	-	-	-	-
VA 5 2-120 - Temp. 90°C Max. Flow 60 lit/min Max. pressure 5,5 bar	-	0	-	-	-	-	-	-	-	-	-	-	-	-
VA 5 1-200 - Temp. 90°C/200°C Max. Flow 60 lit/min Max. pressure 3,5 bar	-	-	●	●	-	-	●	●	-	-	-	-	-	-
VA 5 2-200 - Temp. 90°C/200°C Max. Flow 60 lit/min Max. pressure 5,5 bar	-	-	0	0	-	-	0	0	-	-	-	-	-	-
T-701.200.0009 - Temp. 150°C/200°C Max. Flow 70 lit/min Max. pressure 6 bar	-	-	0	0	-	-	0	0	-	-	-	-	-	-
T-2001.200.0003 - Temp. 90°C/200°C Max. Flow 200 lit/min Max. pressure 5,8 bar	-	-	-	-	-	-	0	0	-	-	●	●	-	-
MD-CX86WT - Temp. 160°C Max. Flow 90 lit/min Max. pressure 6 bar	-	-	-	-	-	-	-	-	-	●	-	-	-	-
MD-CX96WT - Temp. 180°C Max. Flow 100 lit/min Max. pressure 6 bar	-	-	-	-	-	-	-	-	-	-	-	-	-	●
EY2251MK0001 - Temp. 150°C Max. Flow 40 lit/min Max. pressure 5 bar	-	-	-	-	-	●	-	-	-	●	-	-	-	-
EY4281MK0001 - Temp. 150°C Max. Flow 60 lit/min Max. pressure 6 bar	-	-	-	-	-	-	-	-	-	0	-	-	-	-
MD-CX86HT - Temp. 350°C Max. Flow 90 lit/min Max. pressure 6 bar	-	-	-	-	-	-	-	-	-	-	-	-	●	-