TCU • TEMPERATURE CONTROL UNIT

SMART 2A

Oil temperature control unit for industrial aplications up to 150ºC in the field of plastic injection moulding, extrusion, chemical, pharmaceutical, cosmetics or steel.

Oil
FLUID

150ºC
MAX. TEMP.

MAIN FEATURES

- Pump works under pressure
- Solid state relays for heating
- Frontal cooler for solid state relays
- PID temperature control in cooling and heating process
- Hose breakage and leakage monitor
- Sensor failure monitor
- Manual oil filling
- Standard pump 60 l/m 3,8 bar
- Indirect cooling system (submersible coil)
- One solenoide valve for cooling
- Entire heaters, tank, process pipes and thermocouple in stainless steel
- Oil level sensor through stainless steel buoy
- Acoustic alarm
- Castors
- Manometer
- User friendly digital control display

OPTIONS

- *Analogic Input/Output temperature 4...20mA / 0-10 volt* OPT.
- *Pressure transducer* OPT.
- *Thermocouple in process return* OPT.
- *Flow sensor for pumps 60 lit/min SBT 634* OPT.
- *Flow sensor for pumps 70 lit/min SBT 646* OPT.
- *By pass* OPT.

EQUIPMENT TYPE

OIL
OPEN TANK

EQUIPMENT IMAGE

KEY DATA

Oil
Fluid

150 ºC
Max. temp.

400/3/50hz
Power supply

CERTIFICATION
Industry 4.0 Ready

TECHNICAL DATA

PARAMETER	UNIT	SMART 2A
SMART 2A		
Fluid		**Oil**
Maximum temperature	ºC	**150**
PID temperature control heating / cooling		**Yes**
Heating power	kW	**6 – 9**
Cooling power at 15ºC	kW	**20**
Tank capacity	Lit.	**20**
Expansion volume	Lit.	**7**
Pump TM 601.200	Max.Flow Max.Pressure Motor power	**60 lit/min 3,8 bar 0,5 kw**
Pump TM 602.200 OPT	Max.Flow Max.Pressure Motor power	**60 lit/min 5,8 bar 1 kw**
Pump TM 701.200 OPT	Max.Flow Max.Pressure Motor power	**70 lit/min 5,8 bar 1 kw**
Hydraulic process connections	inlet / outlet	**3/4"**
Hydraulic cooling connections	inlet / outlet	**1/2"**
PCB card	Displays	**TG 121**
Thermocouple type		**J type** PT1000 OPT
Dimensions	mm	**325 x 610 x 700h**
Color	RAL	**7016 – 7035**
Max. electrical cabinet temperature	ºC	**40**
Sound pressure level	db (A)	**< 70**
Weight	kg	**40**
Voltage	V/Ph/Hz	**400/3/50hz** 480/3/60hz OPT

Note: Technical data subject to change. For custom specifications, contact the Marse technical department.

PUMP CURVES

601.200 STANDARD



602.200 OPT



701.200 OPT



COOLING CURVES