TCU • TEMPERATURE CONTROL UNIT

SMART 2W

Water temperature control unit for industrial aplications up to 90ºC in the field of plastic injection moulding, extrusion, chemical, pharmaceutical, cosmetics or steel.

Water
FLUID

90ºC
MAX. TEMP.

MAIN FEATURES

- Pump works under pressure and reverse operation feature
- Solid State relays for heating + frontal cooler
- Frontal cooler for solid state relays
- PID temperature control in cooling and heating process
- Hose breakage and leakage monitor
- Sensor failure monitor
- Automatic water filling
- Standard pump 60 l/m 3,8 bar
- Indirect cooling system
- Two independent solenoide valves one for cooling one for filling
- Entire cooling sytem, heaters, tank, process pipes and thermocouple in stainless steel
- Water level sensor through electrode
- Acoustic alarm
- Castors
- Manometer
- User friendly digital control display

OPTIONS

- *Analogic Input/Output temperature 4...20mA / 0-10 volt* OPT.
- *Electronic flow measurement* OPT.
- *Plate exchanger 20 plates (standard 10 plates substitution)* OPT.
- *Plate exchanger 40 plates (standard 10 plates substitution)* OPT.
- *Manual mould drain* OPT.
- *Pressure transducer* OPT.
- *Thermocouple in process return* OPT.

EQUIPMENT TYPE

WATER
WITH TANK

EQUIPMENT IMAGE

KEY DATA

Water
Fluid

90 ºC
Max. temp.

400/3/50hz
Power supply

CERTIFICATION
Industry 4.0 Ready

TECHNICAL DATA

PARAMETER	UNIT	SMART 2W
SMART 2W		
Fluid		**Water**
Maximum temperature	ºC	**90**
PID temperature control heating / cooling		**Yes**
Heating power	kW	**9 – 12 – 18**
Cooling power at 15ºC (E5Tx10)	kW	**65**
Cooling power at 15ºC (E5Tx20) OPT	kW	**90**
Cooling power at 15ºC (E5Tx40) OPT	kW	**120**
Tank capacity	Lit.	**20**
Expansion volume	Lit.	**7**
Pump TM 601.200	Max.Flow Max.Pressure Motor power	**60 lit/min 3,8 bar 0,5 kw**
Pump TM 602.200 OPT	Max.Flow Max.Pressure Motor power	**60 lit/min 5,8 bar 1 kw**
Pump TM 701.200 OPT	Max.Flow Max.Pressure Motor power	**70 lit/min 5,8 bar 1 kw**
Hydraulic process connections	inlet / outlet	**3/4"**
Hydraulic cooling connections	inlet / outlet	**1/2"**
PCB card	Displays	**TG 121**
Thermocouple type		**J type** PT1000 OPT
Dimensions	mm	**325 x 610 x 700h**
Color	RAL	**7016 – 7035**
Max. electrical cabinet temperature	ºC	**40**
Sound pressure level	db (A)	**< 70**
Weight	kg	**40**
Voltage	V/Ph/Hz	**400/3/50hz** 480/3/60hz OPT

Note: Technical data subject to change. For custom specifications, contact the Marse technical department.

PUMP CURVES

601.200 STANDARD



602.200 OPT



701.200 OPT



COOLING CURVES